

Safety Data Sheet according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Version: 1.0 Revision date: 13/12/2022 Issue date: 13/12/2022

MSDS.000157

Argomix H5

I.1. Product identifier		
Product form		: Mixture
Γrade name SDS code		: Argomix H5 : MSDS.000157
		nixture and uses advised against
Relevant identified uses		: Industrial and professional uses. Perform risk assessment prior to use.
Jses advised against		: Consumer use.
		Uses other than those listed above are not supported, contact your supplier for more information on oth
		uses.
.3. Details of the suppli	er of the safety data sheet	
Sapio Produzione Idrogeno O	ssigeno Srl	
/ia S. Pellico, 48		
20900 Monza		
Г +39 039 836068		
<u>www.sapio.it</u> ⁼ -mail address of competent r	person responsible for the SDS	: sds@sapio it
1.4. Emergency telephor	-	
Emergency telephone number		: +39 0295705444 (24/7)
SECTION 2: Hazards i	dentification	
2.1. Classification of the	substance or mixture	
Classification according to I	Regulation (EC) No. 1272/2008	3 [CLP]
Physical hazards	Flammable gases, Category 1	1B H221
	Gases under pressure : Comp	pressed gas H280
Labelling according to Regu	Ilation (EC) No. 1272/2008 [CL	P] :
		GHS02
Signal word (CLP)		: Danger
Hazard statements (CLP)		: H221 - Flammable gas.
		H280 - Contains gas under pressure; may explode if heated.
Precautionary statements (CL	-	· D040. Keen numu from heat het surfeene onerke soor flores and straitering the second straiter
Prevention Response		: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Neshouse		 P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely. P381 - In case of leakage, eliminate all ignition sources.
Storage		: P403 - Store in a well-ventilated place.
2.3. Other hazards		
		Asphyxiant in high concentrations.
		These high concentrations are within the flammability range.
		Not classified as PBT or vPvB.
		The substance/mixture has no endocrine disrupting properties.



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Version: 1.0 Revision date: 13/12/2022 Issue date: 13/12/2022

MSDS.000157

Argomix H5

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Argon	CAS-No.: 7440-37-1 EC-No.: 231-147-0 EC Index-No.: REACH-no: *1	95	Press. Gas (Comp.), H280
hydrogen	CAS-No.: 1333-74-0 EC-No.: 215-605-7 EC Index-No.: 001-001-00-9 REACH-no: *1	5	Flam. Gas 1A, H220 Press. Gas (Comp.), H280

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*3: Registration not required: Substance manufactured or imported < 1t/y.

SECTION 4: First aid measures 4.1. Description of first aid measures Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped. Skin contact : Adverse effects not expected from this product. Eye contact

Ingestion

- Adverse effects not expected from this product.
- : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
5 5	Shutting off the source of the gas is the preferred method of control.Do not use water jet to extinguish.
5.2. Special hazards arising from the substance or	mixture
	 Exposure to fire may cause containers to rupture/explode. None.
5.3. Advice for firefighters	
Specific methods	 Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire. Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Move containers away from the fire area if this can be done without risk.



Special protective equipment for fire fighters

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Version: 1.0 Revision date: 13/12/2022 Issue date: 13/12/2022

MSDS.000157

Argomix H5

: In confined space use self-contained breathing apparatus.

	Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
ECTION 6: Accidental release meas	sures
1. Personal precautions, protective equ	ipment and emergency procedures
or non-emergency personnel	 Act in accordance with local emergency plan. Try to stop release. Evacuate area. Eliminate ignition sources. Ensure adequate air ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

Stay upwind.

For emergency responders

SE

6.1 For

> : Monitor concentration of released product. Consider the risk of potentially explosive atmospheres.

See section 8 of the SDS for more information on personal protective equipment

Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. See section 5.3 of the SDS for more information.

6.2. Environmental precautions

Try to stop release.

6.3. Methods and material for containment and cleaning up

Ventilate area.

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage	
7.4. Descentions for sofe how diam	

7.1. Precautions for safe handling

Safe use of

autorio ioi outo nutria ig	
of the product :	Assess the risk of potentially explosive atmospheres and the need for explosion-proof equipment. Purge air from system before introducing gas. Take precautionary measures against static discharge. Keep away from ignition sources (including static discharges). Consider the use of only non-sparking tools. Ensure equipment is adequately earthed. The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations.
	Ensure the complete gas system was (or is regularily) checked for leaks before use. Do not smoke while handling product.
	Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Avoid suck back of water, acid and alkalis.
	Do not breathe gas. Avoid release of product into work area.



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Version: 1.0 Revision date: 13/12/2022 Issue date: 13/12/2022

MSDS.000157

	Argomix H5
Safe handling of the gas receptacle	: Do not allow backfeed into the container.
	Protect containers from physical damage; do not drag, roll, slide or drop.
	When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to
	transport cylinders.
	Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
	If user experiences any difficulty operating valve discontinue use and contact supplier.
	Never attempt to repair or modify container valves or safety relief devices.
	Damaged valves should be reported immediately to the supplier.
	Keep container valve outlets clean and free from contaminants particularly oil and water.
	Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
	Close container valve after each use and when empty, even if still connected to equipment.
	Never attempt to transfer gases from one cylinder/container to another.
	Never use direct flame or electrical heating devices to raise the pressure of a container.
	Do not remove or deface labels provided by the supplier for the identification of the content of the container.
	Suck back of water into the container must be prevented.
	Open valve slowly to avoid pressure shock.
7.2. Conditions for safe storage, including	ig any incompatibilities
	Segregate from oxidant gases and other oxidants in store.
	All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive
	atmosphere. Observe all regulations and local requirements regarding storage of containers.
	Containers should not be stored in conditions likely to encourage corrosion.
	Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling
	Containers should be stored in the vertical position and property secured to prevent them normaling over.
	Stored containers should be periodically checked for general condition and leakage.
	Keep containers below 50°C in a well ventilated place.
	Store containers in location free from fire risk and away from sources of heat and ignition.
	Keep away from combustible materials.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/person	al protection
8.1. Control parameters	
OEL (Occupational Exposure Limits)	: None available.
DNEL (Derived-No Effect Level)	: None available.
PNEC (Predicted No-Effect Concentration)	: None available.
8.2. Exposure controls	
8.2.1. Appropriate engineering controls	
	Provide adequate general and local exhaust ventilation.
	Product to be handled in a closed system.
	Gas detectors should be used when flammable gases/vapours may be released.
	Consider the use of a work permit system e.g. for maintenance activities.
	Systems under pressure should be regularily checked for leakages.
8.2.2. Individual protection measures, e.g. person	al protective equipment
	A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:
F <i>((((((((((</i>	PPE compliant to the recommended EN/ISO standards should be selected.
Eye/face protection	: Wear safety glasses with side shields.
Skin protection	Standard EN 166 - Personal eye-protection - specifications.
Hand protection	: Wear working gloves when handling gas containers.
	Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Version: 1.0 Revision date: 13/12/2022 Issue date: 13/12/2022

MSDS.000157

	Argomix H5
Other	: Consider the use of flame resistant anti-static safety clothing.
	Standard EN ISO 14116 - Limited flame spread materials.
	Standard EN 1149-5 - Protective clothing: Electrostatic properties.
	Wear safety shoes while handling containers.
	Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
Respiratory protection	: When indicated by a risk assessment, Respiratory Protective Equipment must be used. The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD.
	Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
	Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
Thermal hazards	: None in addition to the above sections.
8.2.3. Environmental exposure controls	
	Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
 Physical state at 20°C / 101.3kPa 	: Gas.
- Colour	: Colourless.
Odour	: Odourless.
	Odour threshold is subjective and inadequate to warn of overexposure.
Melting point / Freezing point	: Not applicable for gases and gas mixtures.
Boiling point	: Not applicable for gas mixtures.
	It is technically not possible to determine the boiling point or range of this mixture. Component with
	lowest boiling point: hydrogen -253 °C
Flammability	: Flammable gas.
Lower explosive limit (LEL)	: Calculated value: 51.50%
Upper explosive limit (UEL)	: No test data or calculation method available.
Flash point	: Not applicable for gases and gas mixtures.
Auto-ignition temperature	: Not known.
	Auto ignition temperature for mixtures is not available. Component with lowest auto-ignition temperature
	: hydrogen 560 °C
Decomposition temperature	: Not applicable.
pH	: Not applicable for gases and gas mixtures.
Viscosity, kinematic	: Not applicable for gases and gas mixtures.
Water solubility [20°C]	: Mixture is partially soluble in water
Partition coefficient n-octanol/water (Log Kow)	: Not available.
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Density and/or relative density	: Not applicable.
Relative vapour density (air=1)	: Heavier than air.
Particle characteristics	: Not applicable for gases and gas mixtures.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Explosion limits Oxidising properties Flammability range not available.No oxidising properties.

9.2.2. Other safety characteristics

Other data

: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Data for mixture are not available.

Stable under normal conditions.



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Version: 1.0 Revision date: 13/12/2022 Issue date: 13/12/2022

MSDS.000157

Argomix H5

10.3. Possibility of hazardous reactions	
	Can form explosive mixture with air.
	May react violently with oxidants.
Reactivity	: This mixture contains components with the following reactivity : Can form explosive mixture with air.
	May react violently with oxidants.
10.4. Conditions to avoid	
	Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
	Avoid moisture in installation systems.
	Avoid moisture in installation systems.
10.5. Incompatible materials	
To:o: meempatible materials	
	Air, Oxidisers.
	For additional information on compatibility refer to ISO 11114.
10.6. Hazardous decomposition products	
	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information <u>11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008</u>

11.1. Information on nazard classes as defined	a in Regulation (EC) No 12/2/2006
Acute toxicity	: No toxicological effects from this product.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.
11.2. Information on other hazards	
Other information	: The substance/mixture has no endocrine disrupting properties.
SECTION 12: Ecological information	
<u>12.1. Toxicity</u>	
Assessment	: No ecological damage caused by this product.
EC50 48h - Daphnia magna [mg/l]	: No data available.
EC50 72h - Algae [mg/l]	: No data available.
LC50 96 h - Fish [mg/l]	: No data available.
12.2. Persistence and degradability	
Assessment	: No ecological damage caused by this product.
12.3. Bioaccumulative potential	
Assessment	: No ecological damage caused by this product.
<u>12.4. Mobility in soil</u>	
Assessment	: No ecological damage caused by this product.



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Version: 1.0 Revision date: 13/12/2022 Issue date: 13/12/2022

MSDS.000157

Argomix H5

12.5. Results of PBT and vPvB assessment	
Assessment	: Not classified as PBT or vPvB.
12.6. Endocrine disrupting properties	
	The substance/mixture has no endocrine disrupting properties.
12.7. Other adverse effects	
Other adverse effects Effect on the ozone layer Effect on global warming	 No known effects from this product. No effect on the ozone layer. Contains greenhouse gas(es).
SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)	 Contact supplier if guidance is required. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at http://www.eiga.eu for more guidance on suitable disposal methods. Do not discharge into any place where its accumulation could be dangerous. Return unused product in original container to supplier. 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.
13.2. Additional information	
	External treatment and disposal of waste should comply with applicable local and/or national regulations.

14.1. UN number or ID number	
In accordance with ADR / RID / IMDG / IATA / ADN	
UN-No.	: 1954
14.2. UN proper shipping name	
Transport by road/rail (ADR/RID)	: COMPRESSED GAS, FLAMMABLE, N.O.S. (hydrogen, Argon)
Transport by air (ICAO-TI / IATA-DGR)	: Compressed gas, flammable, n.o.s. (hydrogen, Argon)
Transport by sea (IMDG)	: COMPRESSED GAS, FLAMMABLE, N.O.S. (hydrogen, Argon)
14.3. Transport hazard class(es)	
Labelling	
	2.1 : Flammable gases.
Transport by road/rail (ADR/RID)	
Class	: 2
Classification code	: 1F
Hazard identification number	: 23
Tunnel Restriction	: B/D - Tank carriage : Passage forbidden through tunnels of category B, C, D and E. Other carriage Passage forbidden through tunnels of category D and E
Transport by air (ICAO-TI / IATA-DGR)	
Class / Div. (Sub. risk(s))	: 2.1
Transport by sea (IMDG)	
Class / Div. (Sub. risk(s))	: 2.1
Emergency Schedule (EmS) - Fire	: F-D
Emergency Schedule (EmS) - Spillage	: S-U
14.4. Packing group	
Transport by road/rail (ADR/RID)	: Not applicable
Transport by air (ICAO-TI / IATA-DGR)	: Not applicable
Transport by sea (IMDG)	: Not applicable
Sapio Produzione Idrogeno Ossigeno Srl	EN (English) MSDS.000157



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Version: 1.0 Revision date: 13/12/2022 Issue date: 13/12/2022

MSDS.000157

Argomix H5			
14.5. Environmental hazards			
Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Transport by sea (IMDG)	: None. : None. : None.		
14.6. Special precautions for user			
Packing Instruction(s) Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Passenger and Cargo Aircraft Cargo Aircraft only Transport by sea (IMDG)	: P200 : Forbidden. : 200. : P200		
Special transport precautions	 Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure there is adequate ventilation. Ensure that containers are firmly secured. Ensure valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. 		
14.7. Maritime transport in bulk according	to IMO instruments		
	Not applicable.		
	ulations/legislation specific for the substance or mixture		
EU-Regulations			

Restrictions on use	: Contains no substance(s) listed on the REACH Candidate List.
Other information, restriction and prohibition regulations	: Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals).
Seveso Directive : 2012/18/EU (Seveso III)	: Covered.
National regulations	
Regulatory reference	: Ensure all national/local regulations are observed.
15.2. Chemical safety assessment	
	A CSA does not need to be carried out for this product.

SECTION 16: Other information

Indication of changes

: Not applicable.



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Version: 1.0 Revision date: 13/12/2022 Issue date: 13/12/2022

MSDS.000157

	Argomix H5
Abbreviations and acronyms	: ATE - Acute Toxicity Estimate
	CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
	REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
	EINECS - European Inventory of Existing Commercial Chemical Substances
	CAS# - Chemical Abstract Service number
	PPE - Personal Protection Equipment
	LC50 - Lethal Concentration to 50 % of a test population
	RMM - Risk Management Measures
	PBT - Persistent, Bioaccumulative and Toxic
	vPvB - Very Persistent and Very Bioaccumulative
	STOT- SE : Specific Target Organ Toxicity - Single Exposure
	CSA - Chemical Safety Assessment
	EN - European Standard
	UN - United Nations
	ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road IATA - International Air Transport Association
	IMDG code - International Maritime Dangerous Goods
	RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
	WGK - Water Hazard Class
	STOT - RE : Specific Target Organ Toxicity - Repeated Exposure UFI : Unique Formula Identifier
Training advice	: Ensure operators understand the flammability hazard.
Further information	: Classification using data from databases maintained by the European Industrial Gases Association
	(EIGA). Data is maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at : http://www.eiga.eu.
	Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).

Full text of H- and EUH-statements	
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Gas 1B	Flammable gases, Category 1B
H220	Extremely flammable gas.
H221	Flammable gas.
H280	Contains gas under pressure; may explode if heated.
Press. Gas (Comp.)	Gases under pressure : Compressed gas

DISCLAIMER OF LIABILITY

 Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
 Details given in this document are believed to be correct at the time of going to press.

Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document

Sapio Produzione Idrogeno Ossigeno Srl