

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SDS_Ind.Mix_049

Argomix E45

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier			
Trade name	: Argomix E45		
SDS code	: SDS_Ind.Mix_049		

Internal reference no.	: 001344		
1.2. Relevant identified uses of the substance or mixture and uses advised against			
Relevant identified uses	: Industrial and professional. Perform risk assessment prior to use. Contact supplier for more information on uses.		
Uses advised against	: Consumer use.		
1.3. Details of the supplier of	of the safety data sheet		
Company identification	: Sapio Produzione Idrogeno Ossigeno Srl Via S. Pellico, 48 20900 Monza - ITALIA +39 039 83981 +39 039 836068 http://www.sapio.it/ sds@sapio.it		
1.4. Emergency telephone number			
Emergency telephone number	: +39 0295705444 (24/7)		
SECTION 2: Hazards i	dentification		
2.1. Classification of the su	bstance or mixture		
Classification according to Reg	Julation (EC) No. 1272/2008 [CLP]		
Physical hazards	Gases under pressure: Compressed gas H280		
2.2. Label elements			
Labelling according to Regulation (EC) No. 1272/2008 [CLP]			

Hazard pictograms (CLP)	
	GHS04
Signal word (CLP)	: Warning
Hazard statements (CLP)	: H280 - Contains gas under pressure; may explode if heated.

Precautionary statements (CLP)

- Storage : P403 - Store in a well-ventilated place.

2.3. Other hazards

Other hazards not contributing to the classification : Asphyxiant in high concentrations.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Argon	CAS-No.: 7440-37-1 EC-No.: 231-147-0 EC Index-No.: Registration-No.: *1	55	Press. Gas (Comp.), H280
Helium	CAS-No.: 7440-59-7 EC-No.: 231-168-5 EC Index-No.: Registration-No.: *1	45	Press. Gas (Comp.), H280

Full text of H-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*2: Registration deadline not expired.

*3: Registration not required: Substance manufactured or imported < 1t/y.



according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SDS_Ind.Mix_049

Argomix E45

SECTION 4: First aid measur	es		
4.1. Description of first aid measure			
- Inhalation	: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.		
- Skin contact	: Adverse effects not expected from this product.		
- Eye contact	: Adverse effects not expected from this product.		
- Ingestion	: Ingestion is not considered a potential route of exposure.		
4.2. Most important symptoms and e	effects, both acute and delayed		
	In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Refer to section 11.		
4.3. Indication of any immediate me	dical attention and special treatment needed		
	None.		
SECTION 5: Firefighting mea	sures		
5.1. Extinguishing media			
- Suitable extinguishing media	: Water spray or fog.		
- Unsuitable extinguishing media	: Do not use water jet to extinguish.		
5.2. Special hazards arising from the	e substance or mixture		
Specific hazards	: Exposure to fire may cause containers to rupture/explode.		
Hazardous combustion products	: None.		
5.3. Advice for firefighters			
Specific methods	: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product.		

Use water spray or fog to knock down fire fumes if possible.

: In confined space use self-contained breathing apparatus.

Move containers away from the fire area if this can be done without risk.

Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

Special protective equipment for fire fighters

	Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.		
SECTION 6: Accidental release meas	sures		
6.1. Personal precautions, protective equipme	ent and emergency procedures		
	Try to stop release. Evacuate area. Wear self-contained breathing apparatus when e Ensure adequate air ventilation. Act in accordance with local emergency plan. Stay upwind. Oxygen detectors should be used when asphyxia	ntering area unless atmosphere is proved to be safe. ating gases may be released.	
6.2. Environmental precautions			
	Try to stop release.		
6.3. Methods and material for containment and cleaning up			
	Ventilate area.		
6.4. Reference to other sections			
	See also sections 8 and 13.		
SECTION 7: Handling and storage			
7.1. Precautions for safe handling			
Safe use of the product	: The product must be handled in accordance with Only experienced and properly instructed person Consider pressure relief device(s) in gas installat Ensure the complete gas system was (or is regu Do not smoke while handling product. Use only properly specified equipment which is s	s should handle gases under pressure. ions.	
Sapio Produzione Idrogeno Ossigeno Srl	EN (English)	Internal reference no.: 001344 2/7	



according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SDS_Ind.Mix_049

	Argomix E45
	Contact your gas supplier if in doubt. Avoid suck back of water, acid and alkalis. Do not breathe gas. Avoid release of product into atmosphere.
Safe handling of the gas receptacle	 Do not allow backfeed into the container. Protect receptacles from physical damage; do not drag, roll, slide or drop. When moving receptacles, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport receptacles. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating receptacle valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the receptacle contents. Suck back of water into the container must be prevented. Open valve slowly to avoid pressure shock.
7.2. Conditions for safe storage, includ	ling any incompatibilities
	Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.
7.3. Specific end use(s)	

None.

8.1. Control parameters	
OEL (Occupational Exposure Limits)	: None available.
DNEL (Derived-No Effect Level)	: None available.
PNEC (Predicted No-Effect Concentration)	: None available.
8.2. Exposure controls	
8.2.1. Appropriate engineering controls	
8.2.2. Individual protection measures, e.	Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Oxygen detectors should be used when asphyxiating gases may be released. Consider the use of a work permit system e.g. for maintenance activities. g. personal protective equipment
	A risk assessment should be conducted and documented in each work area to assess the risks related to t use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:
	PPE compliant to the recommended EN/ISO standards should be selected.
Eye/face protection	: Wear safety glasses with side shields.
	Standard EN 166 - Personal eye-protection - specifications.
Skin protection	
- Hand protection	: Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk.
- Other	: Wear safety shoes while handling containers.
	Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
Respiratory protection	: Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen deficient atmospheres.
	Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
Thermal hazards	: None in addition to the above sections.



according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SDS_Ind.Mix_049

Argomix E45

None necessary.

9.1. Information on basic physical and che	mical properties
Appearance	
Physical state at 20°C / 101.3kPa	: Gas
Colour	Mixture contains one or more component(s) which have the following colour(s):
	Colourless.
Odour	: Odourless.
Odour threshold	: Odour threshold is subjective and inadequate to warn of overexposure.
pH	: Not applicable for gases and gas mixtures.
Melting point / Freezing point	: Not applicable for gas mixtures.
Boiling point	: Not applicable for gas mixtures.
Flash point	: Not applicable for gases and gas mixtures.
Evaporation rate	: Not applicable for gases and gas mixtures.
Flammability (solid, gas)	: Non flammable.
Explosive limits	: Non flammable.
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Vapour density	: Not applicable.
Relative density, gas (air=1)	: Lighter or similar to air.
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for gas mixtures.
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
Viscosity	: No reliable data available.
Explosive properties	: Not applicable.
Oxidising properties	: Not applicable.
9.2. Other information	
Molar mass	: Not applicable for gas mixtures.
Other data	: None.
SECTION 10: Stability and repative	417
SECTION 10: Stability and reactive	ty
10.1. Reactivity	
	No reactivity hazard other than the effects described in sub-sections below.
10.2. Chemical stability	
	Stable under normal conditions.
10.3. Possibility of hazardous reactions	
	None.
10.4. Conditions to avoid	
	Avoid moisture in installation systems.
10.5. Incompatible materials	·
ro.o. incompatible materials	
	For additional information on compatibility refer to ISO 11114.
10.6. Hazardous decomposition products	
	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
SECTION 11: Toxicological inform	ation
11.1. Information on toxicological effects	
Acute toxicity	: No toxicological effects from this product.



according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SDS_Ind.Mix_049

Argomix E45

Aspiration hazard

: Not applicable for gases and gas mixtures.

SECTION 42: Ecological informatic	
SECTION 12: Ecological informatic	pn
12.1. Toxicity	
Assessment	: No ecological damage caused by this product.
EC50 48h - Daphnia magna	: No data available.
EC50 72h - Algae	: No data available.
LC50 96 h - Fish	: No data available.
12.2. Persistence and degradability	
Assessment	: No ecological damage caused by this product.
12.3. Bioaccumulative potential	
Assessment	: No data available.
12.4. Mobility in soil	
Assessment	: Because of its high volatility, the product is unlikely to cause ground or water pollution.
	Partition into soil is unlikely.
12.5. Results of PBT and vPvB assessment	
•	
Assessment	: Not classified as PBT or vPvB.
12.6. Other adverse effects	
Other adverse effects	: No known effects from this product.
Effect on the ozone layer	: None.
Effect on global warming	: No known effects from this product.
SECTION 13: Disposal consideration	ons
13.1. Waste treatment methods	
	May be vented to atmosphere in a well ventilated place.
	Do not discharge into any place where its accumulation could be dangerous.
	Return unused product in original receptacle to supplier.
List of hazardous waste codes (from Commission Decision 2001/118/EC)	: 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.
13.2. Additional information	
	External treatment and disposal of waste should comply with applicable local and/or national regulations.
SECTION 14: Transport information	n
14.1. UN number	
UN-No.	: 1956
14.2. UN proper shipping name	
Transport by road/rail (ADR/RID)	COMPRESSED GAS, N.O.S. (Argon, Helium)
Transport by air (ICAO-TI / IATA-DGR)	Compressed gas, n.o.s. (Argon, Helium)
Transport by sea (IMDG)	COMPRESSED GAS, N.O.S. (Argon, Helium)
14.3. Transport hazard class(es)	
Labelling	
	2.2 : Non-flammable, non-toxic gases.
Transport by road/rail (ADR/RID) Class	: 2
Sania Produzione Idrogeno Ossigeno Stl	EN (English) Internal reference no : 001344



according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Revision date: 04/07/2018 Version: 1.0

SDS_Ind.Mix_049

Argomix E45

Classification code	: 1A		
Hazard identification number	: 20		
Tunnel Restriction	: E - Passage forbidden through tunnels of category E		
Transport by air (ICAO-TI / IATA-DGR)			
Class / Div. (Sub. risk(s))	: 2.2		
Transport by sea (IMDG)			
Class / Div. (Sub. risk(s))	: 2.2		
Emergency Schedule (EmS) - Fire	: F-C		
Emergency Schedule (EmS) - Spillage	: S-V		
14.4. Packing group			
Transport by road/rail (ADR/RID)	: Not applicable		
Transport by air (ICAO-TI / IATA-DGR)	: Not applicable		
Transport by sea (IMDG)	: Not applicable		
14.5. Environmental hazards			
Transport by road/rail (ADR/RID)	: None.		
Transport by air (ICAO-TI / IATA-DGR)	: None.		
Transport by sea (IMDG)	: None.		
14.6. Special precautions for user			
Packing Instruction(s)			
Transport by road/rail (ADR/RID)	: P200		
Transport by air (ICAO-TI / IATA-DGR)			
Passenger and Cargo Aircraft	: 200.		
Cargo Aircraft only	: 200.		
Transport by sea (IMDG)	: P200		
Special transport precautions	: Avoid transport on vehicles where the load space is not separated from the driver's compartment.		
	Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.		
	Before transporting product containers:		
	- Ensure there is adequate ventilation.		
	- Ensure that containers are firmly secured.		
	- Ensure container valve is closed and not leaking.		
	- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.		
	- Ensure valve protection device (where provided) is correctly fitted.		
14.7. Transport in bulk according to Annex			
	Not applicable.		
SECTION 15: Regulatory information	on		
15.1 Safety, health and environmental regu	lations/legislation specific for the substance or mixture		
EU-Regulations			
Restrictions on use	: None.		
Seveso Directive : 2012/18/EU (Seveso III)	: Not covered.		
National regulations			
National legislation	: Ensure all national/local regulations are observed.		

A CSA does not need to be carried out for this product.

: Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

EINECS: European Inventory of Existing Commercial Chemical Substances

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No

Indication of changes

Abbreviations and acronyms

15.2. Chemical safety assessment

SECTION 16: Other information

1907/2006

: ATE: Acute Toxicity Estimate

CAS: Chemical Abstract Service PPE: Personal Protection Equipment



according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SDS_Ind.Mix_049

A	-	x E45
Δrn	omi	Y FAN
	VIIII	A LTJ

	LC50 - Lethal Concentration to 50 % of a test population
	RMM: Risk Management Measures
	PBT - Persistent, Bioaccumulative and Toxic
	vPvB - Very Persistent and Very Bioaccumulative
	STOT- SE: Specific Target Organ Toxicity - Single Exposure
	CSA: Chemical Safety Assessment
	EN: European Standard
	UN: United Nations
	ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
	IATA - International Air Transport Association
	IMDG code - International Maritime Dangerous Goods
	RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
	WGK: Water Hazard Class
	STOT - RE: Specific Target Organ Toxicity - Repeated Exposure
Training advice	: The hazard of asphyxiation is often overlooked and must be stressed during operator training.
	For more guidance, refer to EIGA SL 01 "Dangers of Asphyxiation", downloadable at http://www.eiga.eu
Further information	: Classification using data from databases maintained by the European Industrial Gases Association (EIGA).
	Classification in accordance with the calculation methods of Regulation (EC) 1272/2008 CLP.

Full wording of relevant H Statements and classification codes

Press. Gas (Comp.)	Gases under pressure: Compressed gas
H280	Contains gas under pressure; may explode if heated.
DISCLAIMER OF LIABILITY	 Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
	Details given in this document are believed to be correct at the time of going to press.

Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.