

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SDS_Ind.Mix_111

Argomix O4

SECTION 1: Identification of the substance/mixture and of the company/undertaking	
11 Product identifier	

1.1. Product identifier	
Product form Trade name SDS code Internal reference no.	: Mixture : Argomix O4 : SDS_Ind.Mix_111 : 001724
1.2. Relevant identified uses	s of the substance or mixture and uses advised against
Relevant identified uses	: Industrial and professional. Perform risk assessment prior to use. Contact supplier for more information on uses.
Uses advised against	: Consumer use.
1.3. Details of the supplier of	of the safety data sheet
Company identification	: Sapio Produzione Idrogeno Ossigeno Srl Via S. Pellico, 48 20900 Monza - ITALIA +39 039 83981 +39 039 836068 http://www.sapio.it/ sds@sapio.it
1.4. Emergency telephone n	lumber
Emergency telephone number	: +39 0295705444 (24/7)
2.1. Classification of the sul Classification according to Reg Physical hazards	bstance or mixture ulation (EC) No. 1272/2008 [CLP] Gases under pressure: Compressed gas H280
2.2. Label elements	
Labelling according to Regulati	on (EC) No. 1272/2008 [C] P]
Hazard pictograms (CLP)	GHS04
Signal word (CLP)	: Warning
Hazard statements (CLP)	: H280 - Contains gas under pressure; may explode if heated.
Precautionary statements (CLP)	- Storage · P403 - Store in a well-ventilated place
	- Storage : P403 - Store in a well-ventilated place.
2.3. Other hazards	

Other hazards not contributing to the classification : As

: Asphyxiant in high concentrations.

SECTION 3: Composition/information on ingredients

3.1. Substances

- Not applicable
- 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Argon	CAS-No.: 7440-37-1 EC-No.: 231-147-0 EC Index-No.: Registration-No.: *1	96	Press. Gas (Comp.), H280
Oxygen	CAS-No.: 7782-44-7 EC-No.: 231-956-9 EC Index-No.: 008-001-00-8 Registration-No.: *1	4	Ox. Gas 1, H270 Press. Gas (Comp.), H280

Full text of H-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*2: Registration deadline not expired.

*3: Registration not required: Substance manufactured or imported < 1t/y.



SECTION 4: First aid measures 4.1. Description of first aid measures

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SDS_Ind.Mix_111

Argomix O4

: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and

- Inhalation	 Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact	: Adverse effects not expected from this product.
- Eye contact	: Adverse effects not expected from this product.
- Ingestion	: Ingestion is not considered a potential route of exposure.
4.2. Most important symptoms and	effects, both acute and delayed
	In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Refer to section 11.
4.3. Indication of any immediate me	edical attention and special treatment needed
	None.
SECTION 5: Firefighting mea	sures
5.1. Extinguishing media	
- Suitable extinguishing media	: Water spray or fog.
- Unsuitable extinguishing media	: Do not use water jet to extinguish.
5.2. Special hazards arising from th	, ,
	e substance or mixture
5.2. Special hazards arising from th Specific hazards Hazardous combustion products	, ,
Specific hazards	e substance or mixture : Exposure to fire may cause containers to rupture/explode.
	e substance or mixture : Exposure to fire may cause containers to rupture/explode.

Specific methods	 Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Move containers away from the fire area if this can be done without risk.
Special protective equipment for fire fighters	 In confined space use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.

SECTION 6: Accidental release measure	ures
6.1. Personal precautions, protective equipment	nt and emergency procedures
	Try to stop release. Evacuate area. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Act in accordance with local emergency plan. Stay upwind. Oxygen detectors should be used when asphyxiating gases may be released.
6.2. Environmental precautions	
	Try to stop release.
6.3. Methods and material for containment and	cleaning up
	Ventilate area.
6.4. Reference to other sections	
	See also sections 8 and 13.
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Safe use of the product	 The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularily) checked for leaks before use.



according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SDS_Ind.Mix_111

	305_IIId.WIX_III
	Argomix O4
	Do not smoke while handling product. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature
	Contact your gas supplier if in doubt.
	Avoid suck back of water, acid and alkalis.
	Do not breathe gas.
	Avoid release of product into atmosphere.
Safe handling of the gas receptacle	: Do not allow backfeed into the container.
	Protect receptacles from physical damage; do not drag, roll, slide or drop.
	When moving receptacles, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport receptacles.
	Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
	If user experiences any difficulty operating receptacle valve discontinue use and contact supplier.
	Never attempt to repair or modify container valves or safety relief devices.
	Damaged valves should be reported immediately to the supplier.
	Keep container valve outlets clean and free from contaminants particularly oil and water.
	Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
	Close container valve after each use and when empty, even if still connected to equipment.
	Never attempt to transfer gases from one container to another.
	Never use direct flame or electrical heating devices to raise the pressure of a container.
	Do not remove or deface labels provided by the supplier for the identification of the receptacle contents.
	Suck back of water into the container must be prevented.
	Open valve slowly to avoid pressure shock.
7.2. Conditions for safe storage, inclue	ding any incompatibilities
	Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion.
	Container valve guards or caps should be in place.
	Containers should be stored in the vertical position and properly secured to prevent them from falling over.
	Stored containers should be periodically checked for general condition and leakage.
	Keep container below 50°C in a well ventilated place.
	Store containers in location free from fire risk and away from sources of heat and ignition.
	Keep away from combustible materials.
7.3. Specific end use(s)	

None.

SECTION 8: Exposure controls/p	personal protection
8.1. Control parameters	
OEL (Occupational Exposure Limits)	: None available.
DNEL (Derived-No Effect Level)	: None available.
PNEC (Predicted No-Effect Concentration)	: None available.
8.2. Exposure controls	
8.2.1. Appropriate engineering controls	
8.2.2. Individual protection measures, e.	Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Oxygen detectors should be used when asphyxiating gases may be released. Consider the use of a work permit system e.g. for maintenance activities. g. personal protective equipment
	A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:
	PPE compliant to the recommended EN/ISO standards should be selected.
Eye/face protection	: Wear safety glasses with side shields.
	Standard EN 166 - Personal eye-protection - specifications.
Skin protection	
- Hand protection	: Wear working gloves when handling gas containers.
	Standard EN 388 - Protective gloves against mechanical risk.
- Other	: Wear safety shoes while handling containers.
	Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
Respiratory protection	: Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen- deficient atmospheres.
	Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
Thermal hazards	: None in addition to the above sections.
Sapia Produziona Idragano Oscigano St	EN (English) Internal reference po : 004724 3/7



according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SDS_Ind.Mix_111

Argomix O4

8.2.3. Environmental exposure controls

None necessary.

9.1. Information on basic physical and che	mical properties
Appearance	
Physical state at 20°C / 101.3kPa	: Gas
Colour	 Mixture contains one or more component(s) which have the following colour(s): Colourless.
Odour	: Odourless.
Odour threshold	: Odour threshold is subjective and inadequate to warn of overexposure.
pH	: Not applicable for gases and gas mixtures.
Melting point / Freezing point	: Not applicable for gas mixtures.
Boiling point	: Not applicable for gas mixtures.
Flash point	: Not applicable for gases and gas mixtures.
Evaporation rate	: Not applicable for gases and gas mixtures.
Flammability (solid, gas)	: Non flammable.
Explosive limits	: Non flammable.
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Vapour density	: Not applicable.
Relative density, gas (air=1)	: Heavier than air.
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for gas mixtures.
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
Viscosity	: No reliable data available.
Explosive properties	: Not applicable.
Oxidising properties	: Not applicable.
9.2. Other information	
Molar mass	: Not applicable for gas mixtures.
Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.
SECTION 10: Stability and reactiv	ity
10.1. Reactivity	
	No reactivity hazard other than the effects described in sub-sections below.
10.2. Chemical stability	
	Stable under normal conditions.
10.3. Possibility of hazardous reactions	
	None.
10.4. Conditions to avoid	
	Avoid moisture in installation systems.
10.5. Incompatible materials	
	None. For additional information on compatibility refer to ISO 11114.
10.6. Hazardous decomposition products	
	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information	
11.1. Information on toxicological effect	ts
Acute toxicity	: No toxicological effects from this product.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.



according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SDS_Ind.Mix_111

Argomix O4

SIOI-repeated exposure	
Aspiration hazard	

: No known effects from this product.

: Not applicable for gases and gas mixtures.

12.1. Toxicity	
Assessment	: No ecological damage caused by this product.
EC50 48h - Daphnia magna	: No data available.
EC50 72h - Algae	: No data available.
_C50 96 h - Fish	: No data available.
12.2. Persistence and degradability	
Assessment	: No ecological damage caused by this product.
12.3. Bioaccumulative potential	
Assessment	: No data available.
12.4. Mobility in soil	
Assessment	: Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.
12.5. Results of PBT and vPvB assessment	
Assessment	: Not classified as PBT or vPvB.
12.6. Other adverse effects	
Other adverse effects	: No known effects from this product.
Effect on the ozone layer	: None.
Effect on global warming	: No known effects from this product.
SECTION 13: Disposal consideratio	ns
13.1. Waste treatment methods	
	May be vented to atmosphere in a well ventilated place.
	Do not discharge into any place where its accumulation could be dangerous.
	Return unused product in original receptacle to supplier.
ist of hazardous waste codes (from Commission Decision 2001/118/EC)	: 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.
13.2. Additional information	
	External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information	
14.1. UN number	
UN-No.	: 1956
14.2. UN proper shipping name	
Transport by road/rail (ADR/RID)	[:] COMPRESSED GAS, N.O.S. (Argon, Oxygen)
Transport by air (ICAO-TI / IATA-DGR)	[:] Compressed gas, n.o.s. (Argon, Oxygen)
Transport by sea (IMDG)	COMPRESSED GAS, N.O.S. (Argon, Oxygen)
14.3. Transport hazard class(es)	
Labelling	

2.2 : Non-flammable, non-toxic gases.

Sapio Produzione Idrogeno Ossigeno Srl



according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Revision date: 04/07/2018 Version: 1.0

SDS_Ind.Mix_111

Argomix O4

	-
Class	: 2
Classification code	: 1A
Hazard identification number	: 20
Tunnel Restriction Transport by air (ICAO-TI / IATA-DGR)	: E - Passage forbidden through tunnels of category E
Class / Div. (Sub. risk(s))	: 2.2
Transport by sea (IMDG)	
Class / Div. (Sub. risk(s))	: 2.2
Emergency Schedule (EmS) - Fire	: F-C
Emergency Schedule (EmS) - Spillage	: S-V
14.4. Packing group	
Transport by road/rail (ADR/RID)	: Not applicable
Transport by air (ICAO-TI / IATA-DGR)	: Not applicable
Transport by sea (IMDG)	: Not applicable
14.5. Environmental hazards	
Transport by road/rail (ADR/RID)	: None.
Transport by air (ICAO-TI / IATA-DGR)	: None.
Transport by sea (IMDG)	: None.
14.6. Special precautions for user	
Packing Instruction(s) Transport by road/rail (ADR/RID)	: P200
Transport by road/fail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR)	: P200
Passenger and Cargo Aircraft	: 200.
Cargo Aircraft only	: 200.
Transport by sea (IMDG)	: P200
Special transport precautions	 Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure there is adequate ventilation. Ensure that containers are firmly secured. Ensure container valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted.
14.7. Transport in bulk according to Anno	ex II of MARPOL 73/78 and the IBC Code
	Not applicable.
SECTION 15: Poquiatory informa	ation
SECTION 15: Regulatory informa	
	gulations/legislation specific for the substance or mixture
EU-Regulations	
Restrictions on use	: None.
Seveso Directive : 2012/18/EU (Seveso III)	: Not covered.
National regulations	
National legislation	: Ensure all national/local regulations are observed.
15.2. Chemical safety assessment	
	A CSA does not need to be carried out for this product.
SECTION 16: Other information	
Indication of changes	: Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.
Abbreviations and acronyms	 ATE: Acute Toxicity Estimate CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006 EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstract Service
Sanio Produzione Idrogeno Ossigeno Srl	EN /English) Internal reference on 1 001724 6/7



according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SDS_Ind.Mix_111

Argomix O4

	PPE: Personal Protection Equipment
	LC50 - Lethal Concentration to 50 % of a test population
	RMM: Risk Management Measures
	PBT - Persistent, Bioaccumulative and Toxic
	vPvB - Very Persistent and Very Bioaccumulative
	STOT- SE: Specific Target Organ Toxicity - Single Exposure
	CSA: Chemical Safety Assessment
	EN: European Standard
	UN: United Nations
	ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
	IATA - International Air Transport Association
	IMDG code - International Maritime Dangerous Goods
	RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
	WGK: Water Hazard Class
	STOT - RE: Specific Target Organ Toxicity - Repeated Exposure
Training advice	: The hazard of asphyxiation is often overlooked and must be stressed during operator training.
	For more guidance, refer to EIGA SL 01 "Dangers of Asphyxiation", downloadable at http://www.eiga.eu
Further information	: Classification using data from databases maintained by the European Industrial Gases Association (EIGA).
	Classification in accordance with the calculation methods of Regulation (EC) 1272/2008 CLP.

Full wording of relevant H Statements and classification codes

Ox. Gas 1	Oxidising Gases, Category 1
Press. Gas (Comp.)	Gases under pressure: Compressed gas
H270	May cause or intensify fire; oxidiser.
H280	Contains gas under pressure; may explode if heated.

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press.

Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.