

## Oxygen refrigerated liquid

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

|                        |   |
|------------------------|---|
| Product form           | : Substance   |
| Trade name             | : Oxygen refrigerated liquid                                |
| SDS code               | : 097B  |
| Internal reference no. | : 000400  |
| Chemical description   | : Oxygen  |
| CAS-No.                | : 7782-44-7   |
| EC-No.                 | : 231-956-9   |
| EC Index-No.           | : 008-001-00-8  |
| Registration-No.       | : Listed in Annex IV / V REACH, exempted from registration. |
| Chemical formula       | : O <sub>2</sub>  |

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

|                          |   |
|--------------------------|---|
| Relevant identified uses | : Industrial and professional. Perform risk assessment prior to use.<br>Test gas/Calibration gas.<br>Welding, cutting, heating and brazing.<br>Shield gas for welding processes.<br>Water treatment.<br>Use for manufacture of electronic/photovoltaic components.<br>Laboratory use.<br>Food applications.<br>Contact supplier for more information on uses. |
| Uses advised against     | : Consumer use.   |

#### 1.3. Details of the supplier of the safety data sheet

|                        |   |
|------------------------|---|
| Company identification | : Sapio Produzione Idrogeno Ossigeno Srl<br>Via S. Pellico, 48<br>20900 Monza - ITALIA<br>+39 039 83981   +39 039 836068<br><a href="http://www.sapio.it/">http://www.sapio.it/</a><br>sds@sapio.it |
|------------------------|---|

#### 1.4. Emergency telephone number

|                            |                         |
|----------------------------|-------------------------|
| Emergency telephone number | : +39 0295705444 (24/7) |
|----------------------------|-------------------------|

### SECTION 2: Hazards identification



#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

|                  |  |      |
|------------------|--|------|
| Physical hazards | Oxidising Gases, Category 1                      | H270 |
|                  | Gases under pressure: Refrigerated liquefied gas | H281 |

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

|                                |   |
|--------------------------------|---|
| Hazard pictograms (CLP)        | :     |
|                                | : GHS03      GHS04  |
| Signal word (CLP)              | : Danger  |
| Hazard statements (CLP)        | : H270 - May cause or intensify fire; oxidiser.<br>H281 - Contains refrigerated gas; may cause cryogenic burns or injury.   |
| Precautionary statements (CLP) | : - Prevention : P244 - Keep valves and fittings free from oil and grease.<br>P220 - Keep away from clothing and other combustible materials.<br>P282 - Wear cold insulating gloves and either face shield or eye protection.<br>- Response : P336+P315 - Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.<br>P370+P376 - In case of fire: stop leak if safe to do so.<br>- Storage : P403 - Store in a well-ventilated place. |

## Oxygen refrigerated liquid

### 2.3. Other hazards

Other hazards not contributing to the classification : None.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

| Name                       | Product identifier  | %   | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|----------------------------|---|-----|---|
| Oxygen refrigerated liquid | CAS-No.: 7782-44-7<br>EC-No.: 231-956-9<br>EC Index-No.: 008-001-00-8<br>Registration-No.: *1 | 100 | Ox. Gas 1, H270<br>Press. Gas (Ref. Liq.), H281                 |

Contains no other components or impurities which will influence the classification of the product.

\*1: Listed in Annex IV / V REACH, exempted from registration.

\*2: Registration deadline not expired.

\*3: Registration not required: Substance manufactured or imported < 1t/y.

### 3.2. Mixtures

Not applicable

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area.
- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

### 4.2. Most important symptoms and effects, both acute and delayed

Continuous inhalation of concentrations higher than 75% may cause nausea, dizziness, respiratory difficulty and convulsion.  
Refer to section 11.

### 4.3. Indication of any immediate medical attention and special treatment needed

None.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

### 5.2. Special hazards arising from the substance or mixture

- Specific hazards : Supports combustion.  
Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : None.

### 5.3. Advice for firefighters

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.  
If possible, stop flow of product.  
Use water spray or fog to knock down fire fumes if possible.  
If leaking do not spray water onto container. Water surrounding area (from protected position) to contain fire. Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters : Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.  
Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- Try to stop release.
- Evacuate area.
- Monitor concentration of released product.
- Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
- Eliminate ignition sources.
- Use protective clothing.
- Ensure adequate air ventilation.
- Act in accordance with local emergency plan.

## Oxygen refrigerated liquid

Stay upwind.

### 6.2. Environmental precautions

Try to stop release.  
Liquid spillages can cause embrittlement of structural materials.

### 6.3. Methods and material for containment and cleaning up

Ventilate area.

### 6.4. Reference to other sections

See also sections 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Safe use of the product

: The product must be handled in accordance with good industrial hygiene and safety procedures.  
Only experienced and properly instructed persons should handle gases under pressure.  
Consider pressure relief device(s) in gas installations.  
Ensure the complete gas system was (or is regularly) checked for leaks before use.  
Do not smoke while handling product.  
Keep equipment free from oil and grease.  
Use no oil or grease.  
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature.  
Contact your gas supplier if in doubt.  
Use only oxygen approved lubricants and oxygen approved sealings.  
Use only with equipment cleaned for oxygen service and rated for cylinder pressure.  
Avoid suck back of water, acid and alkalis.  
Do not breathe gas.

Safe handling of the gas receptacle

: Do not allow backfeed into the container.  
Protect receptacles from physical damage; do not drag, roll, slide or drop.  
When moving receptacles, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport receptacles.  
Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.  
If user experiences any difficulty operating receptacle valve discontinue use and contact supplier.  
Never attempt to repair or modify container valves or safety relief devices.  
Damaged valves should be reported immediately to the supplier.  
Keep container valve outlets clean and free from contaminants particularly oil and water.  
Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.  
Close container valve after each use and when empty, even if still connected to equipment.  
Never attempt to transfer gases from one container to another.  
Never use direct flame or electrical heating devices to raise the pressure of a container.  
Do not remove or deface labels provided by the supplier for the identification of the receptacle contents.  
Suck back of water into the container must be prevented.  
Open valve slowly to avoid pressure shock.

### 7.2. Conditions for safe storage, including any incompatibilities

Observe all regulations and local requirements regarding storage of containers.  
Containers should not be stored in conditions likely to encourage corrosion.  
Container valve guards or caps should be in place.  
Containers should be stored in the vertical position and properly secured to prevent them from falling over.  
Stored containers should be periodically checked for general condition and leakage.  
Keep container below 50°C in a well ventilated place.  
Segregate from flammable gases and other flammable materials in store.  
Store containers in location free from fire risk and away from sources of heat and ignition.  
Keep away from combustible materials.

### 7.3. Specific end use(s)

None.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

OEL (Occupational Exposure Limits) : None available.  
DNEL (Derived-No Effect Level) : None available.  
PNEC (Predicted No-Effect Concentration) : None available.

### 8.2. Exposure controls

## Oxygen refrigerated liquid

### 8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation.  
Systems under pressure should be regularly checked for leakages.  
Avoid oxygen rich (>23,5%) atmospheres.  
Gas detectors should be used when oxidising gases may be released.  
Consider the use of a work permit system e.g. for maintenance activities.

### 8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected.

• Eye/face protection

: Wear goggles and a face shield when transfilling or breaking transfer connections.  
Standard EN 166 - Personal eye-protection - specifications.

• Skin protection

- Hand protection

: Wear working gloves when handling gas containers.  
Standard EN 388 - Protective gloves against mechanical risk.  
Wear cold insulating gloves when transfilling or breaking transfer connections.  
Standard EN 511 - Cold insulating gloves.

- Other

: Consider the use of flame resistant safety clothing.  
Standard EN ISO 14116 - Limited flame spread materials.  
Wear safety shoes while handling containers.  
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

• Respiratory protection

: None necessary.

• Thermal hazards

: None in addition to the above sections.

### 8.2.3. Environmental exposure controls

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance

- Physical state at 20°C / 101.3kPa : Gas
- Colour : Bluish liquid.

Odour : No odour warning properties.

Odour threshold : Odour threshold is subjective and inadequate to warn of overexposure.

pH : Not applicable for gases and gas mixtures.

Melting point / Freezing point : -219 °C

Boiling point : -183 °C

Flash point : Not applicable for gases and gas mixtures.

Evaporation rate : Not applicable for gases and gas mixtures.

Flammability (solid, gas) : Non flammable.

Explosive limits : Non flammable.

Vapour pressure [20°C] : Not applicable.

Vapour pressure [50°C] : Not applicable.

Vapour density : Not applicable.

Relative density, liquid (water=1) : 1,1

Relative density, gas (air=1) : 1,1

Water solubility : 39 mg/l

Partition coefficient n-octanol/water (Log Kow) : Not applicable for inorganic gases.

Auto-ignition temperature : Non flammable.

Decomposition temperature : Not applicable.

Viscosity : No reliable data available.

Explosive properties : Not applicable.

Oxidising properties : Oxidiser.

### 9.2. Other information

Molar mass : 32 g/mol

Critical temperature : -118 °C

- Coefficient of oxygen equivalency (Ci) : 1

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

## Oxygen refrigerated liquid

No reactivity hazard other than the effects described in sub-sections below.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Violently oxidises organic material.  
Risk of explosion if spilt on organic structural materials (e.g. wood or asphalt).

### 10.4. Conditions to avoid

Avoid moisture in installation systems.

### 10.5. Incompatible materials

May react violently with combustible materials.  
May react violently with reducing agents.  
Keep equipment free from oil and grease.  
Consider the potential toxicity hazard due to the presence of chlorinated or fluorinated polymers in high pressure (> 30 bar) oxygen lines in case of combustion.  
For additional information on compatibility refer to ISO 11114.  
Materials such as carbon steel, low alloy carbon steel and plastic become brittle at low temperatures and are subject to failure. Use appropriate materials compatible with the cryogenic conditions present in refrigerated liquefied gas systems.  
Consult supplier for specific recommendations.

### 10.6. Hazardous decomposition products

None.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

|                                       |   |
|---------------------------------------|---|
| Acute toxicity                        | : No known toxicological effects from this product. |
| Skin corrosion/irritation             | : No known effects from this product.               |
| Serious eye damage/irritation         | : No known effects from this product.               |
| Respiratory or skin sensitisation     | : No known effects from this product.               |
| Germ cell mutagenicity                | : No known effects from this product.               |
| Carcinogenicity                       | : No known effects from this product.               |
| Toxic for reproduction : Fertility    | : No known effects from this product.               |
| Toxic for reproduction : unborn child | : No known effects from this product.               |
| STOT-single exposure                  | : No known effects from this product.               |
| STOT-repeated exposure                | : No known effects from this product.               |
| Aspiration hazard                     | : Not applicable for gases and gas mixtures.        |

## SECTION 12: Ecological information

### 12.1. Toxicity

|                          |  |
|--------------------------|--|
| Assessment               | : No ecological damage caused by this product. |
| EC50 48h - Daphnia magna | : No data available.                           |
| EC50 72h - Algae         | : No data available.                           |
| LC50 96 h - Fish         | : No data available.                           |

### 12.2. Persistence and degradability

|            |  |
|------------|--|
| Assessment | : No ecological damage caused by this product. |
|------------|--|

### 12.3. Bioaccumulative potential

|            |                      |
|------------|----------------------|
| Assessment | : No data available. |
|------------|----------------------|

### 12.4. Mobility in soil

|            |   |
|------------|---|
| Assessment | : Because of its high volatility, the product is unlikely to cause ground or water pollution.<br>Partition into soil is unlikely. |
|------------|---|

### 12.5. Results of PBT and vPvB assessment

|            |                      |
|------------|----------------------|
| Assessment | : No data available. |
|------------|----------------------|

## Oxygen refrigerated liquid

### 12.6. Other adverse effects

|                           |   |
|---------------------------|---|
| Other adverse effects     | : Can cause frost damage to vegetation. |
| Effect on the ozone layer | : None.                                 |
| Effect on global warming  | : None.                                 |

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Contact supplier if guidance is required.  
 May be vented to atmosphere in a well ventilated place.  
 Do not discharge into any place where its accumulation could be dangerous.  
 Ensure that the emission levels from local regulations or operating permits are not exceeded.  
 Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.eu> for more guidance on suitable disposal methods.  
 Return unused product in original receptacle to supplier.

List of hazardous waste codes (from Commission Decision 2001/118/EC) : 16 05 04 \*: Gases in pressure containers (including halons) containing dangerous substances.

### 13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

## SECTION 14: Transport information

### 14.1. UN number

UN-No. : 1073

### 14.2. UN proper shipping name

Transport by road/rail (ADR/RID) : OXYGEN, REFRIGERATED LIQUID  
 Transport by air (ICAO-TI / IATA-DGR) : Oxygen, refrigerated liquid  
 Transport by sea (IMDG) : OXYGEN, REFRIGERATED LIQUID

### 14.3. Transport hazard class(es)

Labelling :



2.2 : Non-flammable, non-toxic gases.  
 5.1 : Oxidizing substances.

#### Transport by road/rail (ADR/RID)

Class : 2  
 Classification code : 30  
 Hazard identification number : 225  
 Tunnel Restriction : C/E - Tank carriage : Passage forbidden through tunnels of category C, D and E. Other carriage : Passage forbidden through tunnels of category E

#### Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.2 (5.1)  
 Emergency Schedule (EmS) - Fire : F-C  
 Emergency Schedule (EmS) - Spillage : S-W

### 14.4. Packing group

Transport by road/rail (ADR/RID) : Not applicable  
 Transport by air (ICAO-TI / IATA-DGR) : Not applicable  
 Transport by sea (IMDG) : Not applicable

### 14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.  
 Transport by air (ICAO-TI / IATA-DGR) : None.  
 Transport by sea (IMDG) : None.

### 14.6. Special precautions for user

#### Packing Instruction(s)

Transport by road/rail (ADR/RID) : P203

## Oxygen refrigerated liquid

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : Forbidden.

Cargo Aircraft only : Forbidden.

Transport by sea (IMDG) : P203

Special transport precautions

- : Avoid transport on vehicles where the load space is not separated from the driver's compartment.
- Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
- Before transporting product containers:
  - Ensure there is adequate ventilation.
  - Ensure that containers are firmly secured.
  - Ensure container valve is closed and not leaking.
  - Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
  - Ensure valve protection device (where provided) is correctly fitted.

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU-Regulations

Restrictions on use : None.

Seveso Directive : 2012/18/EU (Seveso III) : Listed.

#### National regulations

National legislation : Ensure all national/local regulations are observed.

### 15.2. Chemical safety assessment

A CSA does not need to be carried out for this product.

## SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.

Abbreviations and acronyms : ATE: Acute Toxicity Estimate  
 CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008  
 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 CAS: Chemical Abstract Service  
 PPE: Personal Protection Equipment  
 LC50 - Lethal Concentration to 50 % of a test population  
 RMM: Risk Management Measures  
 PBT - Persistent, Bioaccumulative and Toxic  
 vPvB - Very Persistent and Very Bioaccumulative  
 STOT- SE: Specific Target Organ Toxicity - Single Exposure  
 CSA: Chemical Safety Assessment  
 EN: European Standard  
 UN: United Nations  
 ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
 IATA - International Air Transport Association  
 IMDG code - International Maritime Dangerous Goods  
 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail  
 WGK: Water Hazard Class  
 STOT - RE: Specific Target Organ Toxicity - Repeated Exposure

Training advice : Ensure operators understand the hazard of oxygen enrichment.

DISCLAIMER OF LIABILITY : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.  
 Details given in this document are believed to be correct at the time of going to press.  
 Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.